

HighLine

SX-HL-197-i-BCWv1a

SX-HL-197-i-BGWv1a



indoor Fixed
LED display

Techn. Data LED Screen: UltraLine

| Product Details | SX-HL-197-i-BCWv1a | SX-HL-197-i-BGWv1a |
|--|---------------------------------|--------------------|
| Pixel Pitch (mm) | 1,97 | |
| Physical Density (Pixel/m ²) | 257.874 | |
| LED Arrangement | 1R1G1B | |
| LED Type | SMD 1515 Copper Wire | SMD 1515 Gold Wire |
| Pixelcard Size (mm x mm) | 256 x 288 | |
| Pixelcard Resolution (Pixel) | 130 x 146 | |
| Drive Mode | Constant Current Drive | |
| Scanning Mode | 1/30 | |
| Horizontal Viewing Angle (Deg.) | 140 | |
| Vertical Viewing Angle (Deg.) | 120 | |
| Brightness NIT (cd/m ²) | >800 | >900 |
| Grey Scale | 12 - 16 Bit | |
| Refresh Rate (Hz) | ≤ 3.840 | |
| High Refresh Rate IC Driver | High Refresh | |
| Max Power Consumption (W) | ~390 / sqm | |
| Average Power Consumption (W) | ~130 / sqm | |
| Cabinet Size (mm) | 1024 x 576 | |
| Cabinet Resolution (Pixel) | 640 x 360 | |
| Cabinet Thickness (mm) | ~44 | |
| Weight (Kg) | ~ 20kg / sqm plus wiring | |
| Cabinet Material | Aluminium | |
| Color (Mio) | >16.7 | |
| Serviceability | Front Service | |
| Input Voltage (V) | AC 240V +/- 10% @ 50Hz | |
| Protection Level | IP20 | |
| Working Temperature (°C) | -20° - +50° | |
| Operation Humidity (RH) | 10% - 90% | |
| LED Control System Design | Novastar | |
| Certificates | CE, ROHS, PFC, EMC Class A, LVD | |

We reserve the right to alter technical details without prior notice. 04/2021 TK