

SX-HB-21LCD-FHD1600-GH-1-1



21,5" High Brightness
(LCD) Display FHD

Techn. Daten: SX-HB-21LCD-FHD1600-GH-1-1

Product Details	SX-HB-21LCD-FHD1600-GH-1-1
Description	21,5" TFT LCD, LED Backlight 1600 nits, FHD
Display Area (mm)	467,64 (H) x 268,11 (V)
Brightness NIT	1.600 cd/m ²
Resolution	1920 x 1080 (FHD)
Contrast Ratio	2500 : 1
Pixel Pitch (mm)	0,24825
Pixel Per Inch (PPI)	102
Viewing Angle	178° (H) / 178° (V)
Display Colors	16,7M
Response Time (Typical)	25 ms
AD Board Interface	VGA, DVI-D
Input Power	DC 12V (Power Supply included)
Power Consumption	~49 Watts
OSD Key	4 Keys (Power Switch, Menu, +, -)
OSD Control	Brightness, Color, Contrast, Auto Turing, H/V Position and more
Dimensions (mm)	545 (W) x 370 (H) x 61 (D)
Weight (Net)	~6,12 kg
Mounting Options	VESA 75x75, 100x100
Operating Temperature	0°C – 60°C
Storage Temperature	(-)20°C – (+)60°C
Certificates	CE
IMPORTANT NOTE: to ensure lifelong Quality and work guarantee, designer have to obey manufacturers recommendations for heat dissipation!	

We reserve the right to alter technical details without prior notice. 04/2021 JB