

VisioLine

SX-VL-156-i-AGWv2a

SX-VL-156-i-ACWv2a



Indoor Fixed LED display

Techn. Data LED Screen: VisioLine

| Product Details | SX-VL-156-i-ACWv2a | SX-VL-156-i-AGWv2a |
|--|---------------------------------|--------------------|
| Pixel Pitch (mm) | 1,56 | |
| Physical Density (Pixel/m ²) | 409.600 | |
| LED Arrangement | 1R1G1B | |
| LED Type | SMD 1010 Copperwire | SMD 1010 Goldwire |
| Pixelcard Size (mm) | 250 x 250 | |
| Pixelcard Resolution (Pixel) | 160 x 160 | |
| Drive mode | Constant Drive | |
| Scanning Mode | 1/32 | |
| Horizontal Viewing Angle (Deg.) | 80 | |
| Vertical Viewing Angle (Deg.) | 80 | |
| Brightness NIT (cd/m ²) | >600 | >900 |
| Grey Scale | 12-16 Bit | |
| Refresh Rate (Hz) | ≤ 3840 | |
| High Refresh Rate IC Driver | High Refresh | |
| Max Power Consumption (W) | ~ 570 / sqm | |
| Average Power Consumption (W) | ~ 190 / sqm | |
| Cabinet Size (mm) | 500mm x 500mm | |
| Cabinet Resolution | 320 x 320 | |
| Cabinet Thickness (mm) | 81 | |
| Weight (Kg) | ~ 30kg / qm plus wiring | |
| Cabinet Material | Aluminium | |
| Color (Mio) | >16.7 | |
| Serviceability | Front & Rear Service | |
| Input Voltage (V) | AC 240V +/- 10% @ 50Hz | |
| Protection Level | IP40 Front / IP20 Rear | |
| Working Temperature (°C) | 0° - +40° | |
| Operation Humidity (RH) | 10% - 60% | |
| LED Control System Design | Novastar | |
| Certificates | CE, ROHS, PFC, EMC Class A, LVD | |

We reserve the right to alter technical details without prior notice. 03/2021 TK