

# VisioLine

SX-VL-391-i-AGWv2a

SX-VL-391-i-ACWv2a



## Outdoor Fixed LED display

## Techn. Data LED Screen: VisioLine

Product Details	SX-VL-391-i-AGWv2a	SX-VL-391-i-ACWv2a
Pixel Pitch (mm)	3,91	
Physical Density (Pixel/m <sup>2</sup> )	65.536	
LED Arrangement	1R1G1B	
LED Type	SMD 2020 Gold Wire	SMD 2020 Copper Wire
Pixelcard Size (mm)	250 x 250	
Pixelcard Resolution (Pixel)	64 x 64	
Drive Mode	Constant Drive	
Scanning Mode	1/16	
Horizontal Viewing Angle (Deg.)	170	
Vertical Viewing Angle (Deg.)	150	
Brightness NIT (cd/m <sup>2</sup> )	>900	>1100
Grey Scale	12-16 Bit	
Refresh Rate (Hz)	≤ 3840	
High refresh Rate IC Driver	High Refresh	
Max Power Consumption (W)	~ 360 / sqm	
Average Power Consumption (W)	~ 120 / sqm	
Cabinet Size (mm)	500mm x 1000mm / 500mm x 500mm	
Cabinet Resolution (Pixel)	128 x 128	
Cabinet Thickness (mm)	~81	
Weight (Kg)	~ 30kg / sqm plus wiring	
Cabinet Material	Aluminium	
Color (Mio)	>16.7	
Serviceability	Front & Rear Service	
Input Voltage (V)	AC 240V +/- 10% @ 50Hz	
Protection Level	IP40 Front / IP20 Rear	
Working Temperature (°C)	0° - +40°	
Operation Humidity (RH)	10% - 60%	
LED Control System Design	Novastar	
Certificates	CE, ROHS, PFC, EMC Class A, LVD	

We reserve the right to alter technical details without prior notice. 03/2021 TK