

CreativeLine

SX-CL-250-i



2,5mm indoor fixed LED display

Technical data LED Screen: CreativeLine

ProductDetails	SX-CL-250-i
PixelPitch (mm)	2,50
PhysicalDensity(Pixel/m ²)	160.000
LEDType	SMD
Pixelcard Size (mm)	250 x 250
PixelcardResolution (Pixel)	100 x 100
HorizontalViewingAngle (Deg.)	120
VerticalViewing Angle (Deg.)	120
Brightness NIT (cd/m ²)	Up to 1000 NIT
Grey Scale	12 – 16 bit
RefreshRate (Hz)	≤ 3840
Max Power Consumption (W)	~ 600 / sqm
AveragePower Consumption (W)	~200 / sqm
Cabinet Size (mm)	500x1,000, 500x750, 500x500, 500x250, 250x500, 1,000x250, 250x750, 250x1000, 750x250
CabinetThickness(mm)	~47
Weight(Kg)	~25/ sqm plus Wiring
CabinetMaterial	Aluminium
Serviceability	Front Service / Rear Service (only Version V2)
Input Voltage(V)	AC 240V+/-10% @ 50Hz
ProtectionLevel	IP 20
WorkingTemperature(°C)	-20°-+40°
Operation Humidity (RH)	10% -90%
LEDControl System Design	Novastar
Certificates	CE, ROHS, PFC, EMC Class A, LVD
Options	HDR, Calibration on Module, High Brightness
Versions	V1,V2,V10

We reserve the right to alter technical details without prior notice. 04/2024 JaBl

