

CreativeLine

SX-CL-481-i-ACW



4,8mm indoor fixed
LED display

Technical data LED Screen: CreativeLine

| | |
|--|--|
| ProductDetails | SX-CL-481-i-ACW |
| PixelPitch (mm) | 4,81 |
| PhysicalDensity(Pixel/m ²) | 43.264 |
| LEDType | SMD |
| Pixelcard Size (mm) | 250 x 250 |
| PixelcardResolution (Pixel) | 52 x 52 |
| HorizontalViewingAngle (Deg.) | 120 |
| VerticalViewing Angle (Deg.) | 120 |
| Brightness NIT (cd/m ²) | Up to 1000 NIT |
| Grey Scale | 12 -16 Bit |
| RefreshRate (Hz) | ≤ 3840 |
| Max Power Consumption (W) | ~600 / sqm |
| AveragePower Consumption (W) | ~200 / sqm |
| Cabinet Size (mm) | 500x1,000, 500x750, 500x500, 500x250, 250x500, 1,000x250, 250x750, 250x1000, 750x250 |
| CabinetThickness(mm) | ~47 |
| Weight(Kg) | ~25/ sqm plus Wiring |
| CabinetMaterial | Aluminium |
| Serviceability | Front Service / Rear Service (only Version V2) |
| Input Voltage(V) | AC 240V+/-10% @ 50Hz |
| ProtectionLevel | IP 20 |
| WorkingTemperature(°C) | -20°-+40° |
| Operation Humidity (RH) | 10% -90% |
| LEDControl System Design | Novastar |
| Certificates | CE, ROHS, PFC, EMC Class A, LVD |
| Options | HDR (A8S RV-Card), Calibration on Module, High Brightness |
| Versions | V1,V2,V10 |

We reserve the right to alter technical details without prior notice. 01/2024 JaBl

