

PixelLine

SX-PL-O-444-G



4mm Outdoor Led Display

Technical data LED Screen: PixelLine

| Product Details | SX-PL-444-O-GCW-eco | SX-PL-444-O-GGW |
|---|---|------------------------|
| Pixel Pitch (mm) | 4,44 | |
| Physical Density (Pixel/m ²) | 50.625 | |
| LED Type | SMD Copper Wire | Gold Wire |
| Pixelcard Size (mm) | 480 x 320 | |
| Pixelcard Resolution (Pixel) | 108 x 72 | |
| Drive Mode | Constant Current / Common Cathode | |
| Horizontal Viewing Angle (Deg.) | 140 | |
| Vertical Viewing Angle (Deg.) | 120 | |
| Brightness NIT (cd/m ²) | 4000 | Up to 6500 with Option |
| Grey Scale | 12-16 Bit | |
| Refresh Rate (Hz) | ≤ 3.840 | |
| Max Power Consumption (W/m ²) | ~ 700 | ~ 850 |
| Average Power Consumption (W/m ²) | ~ 230 | ~ 280 |
| Cabinet Size (mm) | 960 x 960 / 960 x 640 / 1440 x 960 / 1440 x 640 | |
| Cabinet Thickness (mm) | ~ 103 | |
| Weight (kg/m ²) | ~35 kg / sqm plus wiring | |
| Cabinet Material | Aluminum | |
| Serviceability | Front- & Rear Service | |
| Input Voltage (V) | AC 240V +/- 10% @ 50Hz | |
| Protection Level | IP 65 Front / IP 54 Rear | |
| Working Temperature (°C) | -20° – +55° | |
| Operation Humidity (RH) | 10% - 90% | |
| LED Control System | Novastar | |
| Certificates | CE, ROHS, PFC, EMC Class A, LVD | |
| Options | High Brightness , Energy Saving | |
| Versions | V1,V2,V10,V13 | |

We reserve the right to alter technical details without prior notice. 04/2024 Jabl

