

PixelLine

SX-PL-O-667-G



6mm Outdoor Led Display

Technical data LED Screen: PixelLine

Product Details	SX-PL-667-O-GCW-eco	SX-PL-667-O-GGW
Pixel Pitch (mm)	6,67	
Physical Density (Pixel/m ²)	22.500	
LED Type	SMD Copper Wire	Gold Wire
Pixelcard Size (mm)	480 x 320	
Pixelcard Resolution (Pixel)	72 x 48	
Drive Mode	Constant Current / Common Cathode	
Horizontal Viewing Angle (Deg.)	140	
Vertical Viewing Angle (Deg.)	120	
Brightness NIT (cd/m ²)	Up to 5.500	7.500 - 10.000 with Option
Grey Scale	12-16 Bit	
Refresh Rate (Hz)	≤ 3.840	
Max Power Consumption (W/m ²)	~ 700	~ 850
Average Power Consumption (W/m ²)	~ 230	~ 280
Cabinet Size (mm)	960 x 960 / 960 x 640 / 1440 x 960 / 1440 x 640	
Cabinet Thickness (mm)	~ 103	
Weight (kg/m ²)	~35 kg / sqm plus wiring	
Cabinet Material	Aluminum	
Serviceability	Front- & Rear Service	
Input Voltage (V)	AC 240V +/- 10% @ 50Hz	
Protection Level	IP 65 Front / IP 54 Rear	
Working Temperature (°C)	-20° – +55°	
Operation Humidity (RH)	10% - 90%	
LED Control System	Novastar	
Certificates	CE, ROHS, PFC, EMC Class A, LVD	
Options	High Brightness , Energy Saving	
Versions	V1,V2,V10,V13	

We reserve the right to alter technical details without prior notice. 04/2024 Jabl

