

# FlexLine

SX-FL-195-i-ACWv10a



## Indoor Flexible Led Display



# Technical data LED Screen: FlexLine

<b>Productdetails</b>	<b>SX-FL-195-i-ACWv10a</b>
PixelPitch (mm)	1,95
PhysicalDensity(Pixel/m <sup>2</sup> )	262.144
LEDArrangement	1R1G1B
LEDType	SMD1515 Copperwire
PixelcardSize (mm)	250 x 250
PixelcardResolution (Pixel)	128 x 128
DriveMode	ConstantDrive
Scanning Mode	1/32
HorizontalViewingAngle (Deg.)	120
VerticalViewing Angle (Deg.)	120
Brightness NIT (cd/m <sup>2</sup> )	~1.000 NIT
Grey Scale	14 -16 Bit
RefreshRate (Hz)	≤3840
HighRefresh Rate IC Driver	High Refresh
Max Power Consumption (W)	~600 / sqm
AveragePower Consumption (W)	~200 / sqm
Weight(Kg/m <sup>2</sup> )	~34 KG witch cabinet Frame
CabinetMaterial	Aluminium / Steel / Project related
Color(Mio)	>16.7
Serviceability	Front Service
Input Voltage(V)	AC 240V+/-10% @ 50Hz
ProtectionLevel	IP30
WorkingTemperature(°C)	-20°-+40°
Operation Humidity (RH)	10% -90%
LEDControl System Design	Novastar
Options:	External Controlbox for more Flexibility
Certificates	CE, ROHS, PFC, EMC Class A, LVD

We reserve the right to alter technical details without prior notice. 01/2024 JaBl



Pictures:

