

FlexLine

SX-FL-313-i-ACWv10a



Indoor Flexible Led Display



Technical data LED Screen: FlexLine

Productdetails	SX-FL-313-i-ACWv10a
PixelPitch (mm)	3,13
PhysicalDensity(Pixel/m2)	102.400
LEDArrangement	1R1G1B
LEDType	SMD2020 Copperwire
PixelcardSize (mm)	250 x 250
PixelcardResolution (Pixel)	80 x 80
DriveMode	ConstantDrive
Scanning Mode	1/20
HorizontalViewingAngle (Deg.)	120
VerticalViewing Angle (Deg.)	120
Brightness NIT (cd/m2)	~ 1000 Nit
Grey Scale	14 -16 Bit
RefreshRate (Hz)	≤3840
HighRefresh Rate IC Driver	High Refresh
Max Power Consumption (W)	~600 / sqm
AveragePower Consumption (W)	~200 / sqm
Weight(Kg/m²)	~34 KG witch cabinet Frame
CabinetMaterial	Aluminium / Steel / Project related
Color(Mio)	>16.7
Serviceability	Front Service
Input Voltage(V)	AC 240V+/-10% @ 50Hz
ProtectionLevel	IP30
WorkingTemperature(°C)	-20°-+40°
Operation Humidity (RH)	10% -90%
LEDControl System Design	Novastar
Options:	External Controlbox for more Flexibility
Certificates	CE, ROHS, PFC, EMC Class A, LVD

We reserve the right to alter technical details without prior notice. 01/2024 JaBI



Pictures:

