

MaxLine

SX-ML-390-O-AGWv13a



Outdoor Fixed Led Display



Technical data LED Screen: MaxLine

Product Details	SX-ML-390-O-AGWv13a
Pixel Pitch (mm)	3,90
Physical Density (Pixel/m2)	65536
LED Arrangement	1R1G1B
LED Type	SMD1516 Gold Wire
Pixelcard Size (mm)	250 x 250
Pixelcard Resolution (Pixel)	64 x 64
Drive Mode	Constant Current Drive
Scanning Mode	1/16
Horizontal Viewing Angle (Deg.)	160
Vertical Viewing Angle (Deg.)	150
Brightness NIT (cd/m2)	> 6000
Grey Scale	12-16 Bit
Refresh Rate (Hz)	≤ 3.840
High Refresh Rate IC Driver	High Refresh
Max Power Consumption (W/m2)	~ 780
Average Power Consumption (W/m2)	~ 260
Cabinet Size (mm)	500 x 500 / 500 x 750 / 500 x 1000
Cabinet Resolution (Pixel)	128 x 128 / 128 x 192 / 128 x 256
Cabinet Thickness (mm)	~ 94
Weight (kg/m2)	~32 kg / sqm plus wiring
Cabinet Material	Aluminum
Color (Mio.)	>16.7
Serviceability	Front- & Rear Service
Input Voltage (V)	AC 240V +/- 10% @ 50Hz
Protection Level	IP 55
Working Temperature (°C)	-20° – +50°
Operation Humidity (RH)	10% - 90%
LED Control System Design	Novastar
Certificates	CE, ROHS, PFC, EMC Class A, LVD

We reserve the right to alter technical details without prior notice. 01/2024 TKi

