

MaxLine

SX-ML-481-O-AGWw1a



Outdoor Fixed Led Display



Technical data LED Screen: MaxLine

Product Details	SX-ML-481-O-AGWv1a
Pixel Pitch (mm)	4,81
Physical Density (Pixel/m2)	43.264
LED Arrangement	1R1G1B
LED Type	SMD1921 Gold Wire
Pixelcard Size (mm)	250 x 250
Pixelcard Resolution (Pixel)	52 x 52
Drive Mode	Constant Current Drive
Scanning Mode	1/13
Horizontal Viewing Angle (Deg.)	150
Vertical Viewing Angle (Deg.)	120
Brightness NIT (cd/m2)	> 5500
Grey Scale	12-16 Bit
Refresh Rate (Hz)	≤ 3.840
High Refresh Rate IC Driver	High Refresh
Max Power Consumption (W/m2)	~ 800
Average Power Consumption (W/m2)	~ 200
Cabinet Size (mm)	500 x 1000/750/500
Cabinet Resolution (Pixel)	104 x 208/156/104
Cabinet Thickness (mm)	~ 94
Weight (kg/m2)	~32 kg / sqm plus wiring
Cabinet Material	Aluminum
Color (Mio.)	>16.7
Serviceability	Front- & Rear Service
Input Voltage (V)	AC 240V +/- 10% @ 50Hz
Protection Level	IP 65/54
Working Temperature (°C)	-20° – +50°
Operation Humidity (RH)	10% - 90%
LED Control System Design	Novastar
Certificates	CE, ROHS, PFC, EMC Class A, LVD

We reserve the right to alter technical details without prior notice. 02/2024 JaBl

