


FlexLine

SX-FL-195-i-ACWv10a



Indoor Flexible LED display

Techn. Daten LED Screen: FlexLine

Product details	SX-FL-195-i-ACWv10a
Pixel Pitch (mm)	1,95
Physical Density (Pixel/m2)	262.144
LED Arrangement	1R1G1B
LED Type	SMD1515 Copperwire
Pixelcard Size (mm)	250 x 250
Pixelcard Resolution (Pixel)	128 x 128
Drive Mode	Constant Drive
Scanning Mode	1/32
Horizontal Viewing Angle (Deg.)	120
Vertical Viewing Angle (Deg.)	120
Brightness NIT (cd/m2)	~1.000 NIT
Grey Scale	14 -16 Bit
Refresh Rate (Hz)	≤3840
High Refresh Rate IC Driver	High Refresh
Max Power Consumption (W)	~600 / sqm
Average Power Consumption (W)	~200 / sqm
Weight (Kg/m²)	~34 KG witch cabinet Frame
Cabinet Material	Aluminium
Color (Mio)	>16.7
Serviceability	Front Service
Input Voltage (V)	AC 240V +/- 10% @ 50Hz
Protection Level	IP30
Working Temperature (°C)	-20° - +40°
Operation Humidity (RH)	10% - 90%
LED Control System Design	Novastar
Options:	External Controlbox for more Flexibility
Certificates	CE, ROHS, PFC, EMC Class A, LVD

We reserve the right to alter technical details without prior notice. 09/22JS

Pictures:

