

MaxLine

SX-ML-260-O-ACWv10a



Outdoor Fixed LED display

Techn. Data LED Screen: MaxLine

Product Details	SX-ML-260-O-ACWv10a
Pixel Pitch (mm)	2,60
Physical Density (Pixel/m2)	147.456
LED Arrangement	1R1G1B
LED Type	SMD1515 Copper Wire
Pixelcard Size (mm)	250 x 250
Pixelcard Resolution (Pixel)	96 x 96
Drive Mode	Constant Current Drive
Scanning Mode	1/16
Horizontal Viewing Angle (Deg.)	140
Vertical Viewing Angle (Deg.)	120
Brightness NIT (cd/m2)	>4500
Grey Scale	12 - 16 Bit
Refresh Rate (Hz)	≤ 3.840
High Refresh Rate IC driver	High Refresh
Max Power Consumption (W)	~700 / sqm
Average Power Consumption (W)	~210 / sqm
Cabinet Size (mm)	500 x 500 or custom
Cabinet Resolution (Pixel)	192 x 192 / custom
Cabinet Thickness (mm)	~92
Weight (Kg)	~ 36kg / sqm plus wiring
Cabinet Material	Aluminium
Color (Mio)	>16.7
Serviceability	Front- & Rear Service
Input Voltage (V)	AC 240V +/- 10% @ 50Hz
Protection Level	IP65
Working Temperature (°C)	-20° - +50°
Operation Humidity (RH)	10% - 85%
LED Control System Design	Novastar
Certificates	CE, ROHS, PFC, EMC Class A, LVD
Options	GOB Front

We reserve the right to alter technical details without prior notice. 09/2024 TK