

# VisioLine

SX-VL-260-i-AGWv2a

SX-VL-260-i-ACWv2a



indoor Fixed  
LED display

## Techn. Data LED Screen: VisioLine

Product Details	SX-VL-260-i-AGWv2a	SX-VL-260-i-ACWv2a
Pixel Pitch (mm)	2,60	
Physical Density (Pixel/m <sup>2</sup> )	147.456	
LED Arrangement	1R1G1B	
LED Type	SMD 2020 Gold Wire	SMD 2020 Copperwire
Pixelcard Size (mm)	250 x 250	
Pixelcard Resolution (Px)	96 x 96	
Drive Mode	Constant Drive	
Scanning Mode	1/24	
Horizontal Viewing Angle (Deg.)	140	
Vertical Viewing Angle (Deg.)	100	
Brightness (cd/m <sup>2</sup> )	>1100	>900
Grey Scale	12-16 Bit	
Refresh Rate (Hz)	≤ 3840	
High Refresh Rate IC driver	High Refresh	
Max Power Consumption (W)	~ 440 / sqm	
Average Power Consumption (W)	~ 150 / sqm	
Cabinet Size (mm)	500mm x 1000mm / 500mm x 500mm	
Cabinet Resolution (Pixel)	192 x 384 / 192 x 192	
Cabinet Thickness (mm)	~81	
Weight (Kg)	~ 30kg / sqm plus wiring	
Cabinet Material	Aluminium	
Color (Mio)	>16.7	
Serviceability	Front & Rear Service	
Input Voltage (V)	AC 240V +/- 10% @ 50Hz	
Protection Level	IP40 Front / IP20 Rear	
Working Temperature (°C)	0° - +40°	
Operation Humidity (RH)	10% - 60%	
LED Control System Design	Novastar	
Certificates	CE, ROHS, PFC, EMC Class A, LVD	

We reserve the right to alter technical details without prior notice. 03/2021 TK